

# MANNINGTON COMMERCIAL

## V- 11 Vinyl Composition Tile (VCT) Adhesive

### **Description:**

V-11 is a premium latex adhesive developed specifically for installing Mannington Commercial Vinyl Composition Tile. V-11 is nonflammable and provides a strong moisture resistant and alkali-resistant bond. You may use it on all approved wood underlayments and on-, above-, or below-grade concrete substrates.

### **Features:**

- \* Easy application.
- \* VOC compliant / solvent-free / low odor
- \* Non-flammable
- \* Moisture and alkali resistant
- \* Readily identifiable Mylar chips
- \* Contains fungicide protection
- \* Complies with SCAQMD Rule 1168

### **Directions:**

Make sure the underfloor is clean and free of all foreign matter such as dirt, paint, oil, wax, old adhesives, etc. It must be smooth and level. Sand off any high spots and fill low spots with the appropriate Mannington patching compound. Keep the adhesive, floor covering, and jobsite at a minimum of 65°F for at least 48 hours before, during, and after the installation. The building must have permanent hear /air.

Apply V-11 with a trowel notched 1/16 wide, 1/32 deep, and 1/32 apart in an even and uniform thickness. V-11 can also be applied using a roller or a brush. After spreading, let the adhesive dry. Normal drying time is approximately 45-50 minutes. High humidity and lower temperatures may extend that time.

When placing tiles, set them firmly against adjoining tiles and press into the adhesive. Do not slide tiles into place.

You can remove fresh adhesive with water. Dried adhesive can be removed with mineral spirits.

**Coverage:** Approximately 250-300 sq. ft. per gallon.

**Packaging:** 4-Gallon Pail #849814  
1-Gallon Pail #849811 (4 per carton)

### **Precautions:**

- \* Do not use where **excessive** moisture, alkali, or hydrostatic pressure exists.
- \* Use with adequate ventilation.
- \* Avoid contact with eyes.
- \* Do not ingest.
- \* **KEEP OUT OF THE REACH OF CHILDREN.**