

DESCRIPTION

V-81 is a solvent-free premium latex adhesive developed specifically for use with Mannington Commercial's commercial-grade Resilient sheet product which has a felt backing. V-81 is non-flammable, light-colored, and provides a strong moisture- and alkali-resistant bond. You may use it over all approved suspended wood underlayments and on, above, or below-grade concrete substrates. Refer to Mannington Professional Installation Guide.

FEATURES

- Easy application
- VOC-compliant / solvent-free / low odor
- Non-flammable
- Moisture- and alkali-resistant
- Readily identifiable mylar chips
- Contains fungicide protection
- Complies with SCAQMD Rule 1168

DIRECTIONS

- Make sure the underfloor is clean and free of all foreign matter such as dirt, paint, oil, wax, etc. It should be smooth and level. Sand off high spots and fill low spots, cracks, holes, etc., with the appropriate Mannington patching compound.
- The building must have permanent heat / air.
- Maintain the adhesive, floor covering, and jobsite at a temperature of at least 65°F for a minimum of 48 hours before, during, and after the installation.
- On porous underfloors, apply the adhesive with a trowel having notches 1/16" wide, 1/16" deep, spaced 1/16" apart.
- On non-porous underfloors, apply a thinner spread of adhesive using a trowel with notches 1/16" wide, 1/32" deep and 1/32" apart.
- Provide adhesive open time but do not allow the adhesive to "skin over" before laying the floor covering into the adhesive.
- Immediately roll the adhered material in both directions using a 100- or 150-lb, three-section floor roller.
- You can clean fresh adhesive smears with water. Remove dried adhesive with mineral spirits.
- Avoid heavy traffic on the finished floor for at least 24 hours.

COVERAGE

Approximately 135-180 square feet per gallon.

PACKAGING

1-Gallon Pail #849846, weighs 9.2 lbs (4.17 kg) / 4 per carton
 4-Gallon Pail #849845, weighs 41.4 lbs (18.78 kg)

PRECAUTIONS

- Do not use with Perimiflex or any other vinyl-backed materials.
- Do not use where **excessive** moisture, alkali, or hydrostatic pressure exists.
- Use with adequate ventilation.
- Avoid contact with eyes.
- Do not ingest.
- **KEEP OUT OF THE REACH OF CHILDREN.**